

LMB Series

		Resin retainer		Nominal shaft diameter		d _r										Major dimensions and tolerance										Eccentricity		Radial clearance	Radial load rating(N)						
LMB...CU	Ball (mm)	Weight(Kg)	LMB...UU-AJ	Ball (mm)	Weight	LMB...UU-OP	Ball (mm)	Weight(Kg)	Inch	mm	mm	Precision(Inch)	Precision(gm)	High(Inch)	High(gm)	D(Inch/mm)	D Tolerance (3σ)(Inch)	D Tolerance (3σ)(mm)	L Tolerance (3σ)(Inch)	L Tolerance (3σ)(mm)	B Tolerance (3σ)(Inch)	B Tolerance (3σ)(mm)	W(Inch/mm)	D1(Inch/mm)	b(Inch/mm)	h1(Inch/mm)	θ	Precision	High	Radial Clearance (Max)	Dynamic	Static			
LMB6CU	4	14	LMB6CU-AJ	4	13.5	—	—	—	3/8	9.525	9.525	0-.00025	0/-4	0-.00040	0/-9	.6250(15.875)	0-.00050	0/-13	.8750(22.225)	0-.008	0/-200	.6358(16.15)	0-.008	0/-200	.6390(0.992)	.580(14.935)	.04(1)	—	—	.0003(8)	.0005(12)	-.0001(3)	225	314	
LMB8CU	4	17	LMB8CU-AJ	4	16.5	LMB8CU-OP	3	28	1/2	12.7	0.5	12.7	0-.00025	0/-4	0-.00040	0/-9	.8750(22.225)	0-.00050	0/-13	1.2500(31.750)	0-.008	0/-200	.9625(24.46)	0-.008	0/-200	.9430(1.148)	.820(20.833)	.06(1.5)	.34(7.875)	80°	.0003(8)	.0005(12)	-.0001(3)	510	784
LMB8	4	8	LMB8-AJ	4	7.5	—	—	—	1/4	6.35	0.25	6.35	0-.00025	0/-4	0-.00040	0/-9	.5000(12.700)	0-.00045	0/-11	.7500(19.050)	0-.008	0/-200	.5110(12.98)	0-.008	0/-200	.6390(0.992)	.46(7)1.906	.04(1)	—	—	.0003(8)	.0005(12)	-.0001(3)	206	285
LMB10CU	4	76	LMB10CU-AJ	4	74	LMB10CU-OP	3	57	5/8	15.875	0.625	15.875	0-.00025	0/-4	0-.00040	0/-9	1.1250(28.375)	0-.00050	0/-13	1.2500(31.750)	0-.008	0/-200	1.1199(28.64)	0-.008	0/-200	.850(1.422)	1.059(26.499)	.06(1.5)	.37(9.525)	80°	.0003(8)	.0005(12)	-.0001(3)	774	1180
LMB12CU	5	95	LMB12CU-AJ	5	93	LMB12CU-OP	4	76	3/4	19.05	0.75	19.05	0-.00030	0/-7	0-.00040	0/-10	1.3750(34.938)	0-.00055	0/-16	1.6250(41.275)	0-.008	0/-200	1.1637(29.41)	0-.008	0/-200	.850(1.422)	1.176(29.876)	.06(1.5)	.43(75)1.1125	60°	.0004(10)	.0006(15)	-.0002(3)	862	1270
LMB16CU	6	200	LMB16CU-AJ	6	198	LMB16CU-OP	5	170	1	25.4	1	25.4	0-.00030	0/-7	0-.00040	0/-10	1.6875(42.853)	0-.00065	0/-16	2.2500(57.150)	0-.012	0/-300	1.7547(44.37)	0-.012	0/-300	.867(1.727)	1.468(37.306)	.06(1.5)	.56(25)1.43875	50°	.0004(10)	.0006(15)	-.0002(3)	880	1370
LMB20CU	6	440	LMB20CU-AJ	6	430	LMB20CU-OP	5	370	1-1/4	31.75	1.25	31.75	0-.00035	0/-8	0-.00050	0/-12	1.8750(47.625)	0-.00075	0/-19	2.6250(66.675)	0-.012	0/-300	2.0047(50.92)	0-.012	0/-300	.867(1.727)	1.885(47.904)	.10(2.5)	.62(25)1.875	50°	.0005(12)	.0008(20)	-.0003(8)	1570	2740
LMB24CU	6	670	LMB24CU-AJ	6	660	LMB24CU-OP	5	570	1-1/2	38.1	1.5	38.1	0-.00035	0/-8	0-.00050	0/-12	2.1250(53.938)	0-.00075	0/-19	3.0000(76.200)	0-.012	0/-300	2.4118(61.26)	0-.012	0/-300	.868(1.728)	2.238(56.870)	.12(3)	.75(29.05)	50°	.0005(12)	.0008(20)	-.0003(8)	2180	4020
LMB32CU	6	1140	LMB32CU-AJ	6	1120	LMB32CU-OP	5	980	2	50.8	2	50.8	0-.00035	0/-8	0-.00050	0/-12	2.6250(66.625)	0-.00090	0/-22	4.0000(101.600)	0-.012	0/-300	3.1917(81.07)	0-.012	0/-300	1.029(2.616)	2.837(72.085)	.12(3)	1.0(25.40)	50°	.0007(17)	.0010(25)	-.0005(13)	3820	7940