

Tapered roller thrust bearing TTC, TTCS, TTCL series

| Onderdeel nummer: | | Dimensions(mm/in.) | | | | | Steering Pivot Rating(N/lbf) | Bearing Weight(kg/lbs.) |
|---|--------------------------------------|---------------------------|----------|----------|----------|----------|---|------------------------------------|
| No Oil Holes In Retainer | Oil Holes In Retainer | Fig. | d | D | T | R | | |
| T127 | T127W | C | 32.004 | 66.675 | 19.446 | 0.8 | 42200 | 0.31 |
| T127 | | C | 1.26 | 2.625 | 0.7656 | 0.03 | 9450 | 0.68 |
| T128 | | D | 32.004 | 66.675 | 18.654 | 0.8 | 42200 | 0.29 |
| T128 | | D | 1.26 | 2.625 | 0.7344 | 0.03 | 9450 | 0.64 |
| T130 | | C | 27.102 | 66.675 | 19.446 | 0.8 | 42200 | 0.34 |
| T130 | | C | 1.067 | 2.625 | 0.7656 | 0.03 | 9450 | 0.75 |
| T136 | | D | 35.179 | 66.675 | 18.654 | 0.8 | 42200 | 0.28 |
| T136 | | D | 1.385 | 2.625 | 0.7344 | 0.03 | 9450 | 0.62 |
| T138 | T138W | C | 35.179 | 66.675 | 19.446 | 0.8 | 42200 | 0.30 |
| T138 | | C | 1.385 | 2.625 | 0.7656 | 0.03 | 9450 | 0.66 |
| T138XS | | SPCL(1) | 35.179 | 66.675 | 19.446 | 0.8 | 42200 | ** |
| T138XS | | SPCL(1) | 1.385 | 2.625 | 0.7656 | 0.03 | 9450 | 0 |
| T144 | T144W | C | 36.754 | 66.675 | 19.446 | 1.5 | 42200 | 0.29 |
| T144 | | C | 1.447 | 2.625 | 0.7656 | 0.06 | 9450 | 0.64 |
| T144XA | | SPCL(1) | 36.754 | 66.675 | 19.446 | 1.5 | 42200 | ** |
| T144XA | | SPCL(1) | 1.447 | 2.625 | 0.7656 | 0.06 | 9450 | 0 |
| T151 | T151W | C | 38.354 | 72.619 | 21.433 | 0.8 | 47000 | 0.37 |
| T151 | | C | 1.51 | 2.859 | 0.8438 | 0.03 | 10600 | 0.82 |
| T152 | | D | 38.354 | 72.619 | 20.638 | 0.8 | 47000 | 0.35 |
| T152 | | D | 1.51 | 2.859 | 0.8125 | 0.03 | 10600 | 0.77 |
| T157 | T157W | C | 39.954 | 72.619 | 21.433 | 0.8 | 47000 | 0.37 |
| T157 | | C | 1.573 | 2.859 | 0.8438 | 0.03 | 10600 | 0.82 |
| T163 | T163W | C | 41.529 | 72.619 | 21.433 | 0.8 | 47000 | 0.35 |
| T163 | | C | 1.635 | 2.859 | 0.8438 | 0.03 | 10600 | 0.77 |
| T163X | T163XW | C | 41.529 | 72.619 | 21.433 | 2.0 | 47000 | 0.35 |
| T163X | | C | 1.635 | 2.859 | 0.8438 | 0.8 | 10600 | 0.77 |

Tapered roller thrust bearing TTC, TTCS, TTCL series

| | | | | | | | | |
|------|-------|---|--------|--------|--------|------|-------|------|
| T169 | T169W | C | 43.104 | 82.956 | 23.812 | 0.8 | 64000 | 0.55 |
| T169 | | C | 1.697 | 3.266 | 0.9375 | 0.03 | 14300 | 1.21 |
| T176 | T176W | C | 44.704 | 82.956 | 23.812 | 0.8 | 64000 | 0.54 |
| T176 | | C | 1.76 | 3.266 | 0.9375 | 0.03 | 14300 | 1.19 |